


MacroBin® 26 Series



26-a-FV The MacroBin 26-a-FV and the full 26 Series product line are produced with the latest high-pressure injection molding technology for greater durability.

The MacroBin 26 Series, Macro Plastics' most popular line of bulk harvest and storage bins, is designed with a square footprint to hold up to 1,300 pounds. With double-wall corner and center posts, and two full-length feet with a positive interlocking feature, these bins are durable, yet still lightweight and easy to handle.



The 26 Series has two additional model variations; the MacroBin 26-b-FV and the 26-c-FV.

Inquire with your Macro Plastics Sales Representative as to which bin best suits your needs.

Feature Highlights

- **Impact-grade plastic** lasts longer, standing up to heavy day-to-day use, season after season. The molded plastic resists splintering, reducing damage to product and maintenance costs. Bin repair is inexpensive with hot air welding.
- **Lightweight construction** reduces shipping costs and makes MacroBins easier to move; their interlocking foot design makes them safer to stack — up to 10 high.*
- **FDA-approved materials** are certified safe for use with food products, eliminating many HACCP problems associated with wood bins.
- **Ventilation slots** facilitate the use of thermofogging, reduce heat absorption and cooling costs, and provide for quicker drying and degreening. Narrow vents are also available in the 26-a-FV.
- **Nonporous surfaces** won't absorb water or dehydrate your product like wood bins, and they provide a constant tare weight throughout their use.
- **Rounded corners and smooth surfaces** mean fewer scuffs, abrasions, and cuts on your product. Risk of contamination is reduced because there are fewer places for unwanted particles to hide.
- **Easy-to-sanitize** MacroBins keep cleaning costs to a minimum. A high-pressure wash removes most debris; a nonabrasive brush can dislodge any remaining items.







*See reverse for maximum stack weight specifications.



MACROPLASTICS™
Inventing Fresh Ideas.

800.845.6555 www.macroplastics.com

Benefits of Using MacroBins

<p>Increased productivity.</p>  <p>MacroBins are easy to handle, move, and transport; the unique interlocking foot design makes them easy to align, stack, and store.</p>	<p>Reduced cooling costs.</p>  <p>Hundreds of ventilation slots in the sides and base promote air flow and help your products cool down faster.</p>	<p>Reduced bin repair costs.</p>  <p>MacroBins are virtually maintenance free; repairs are easy with hot air welding.</p>
<p>Better sanitation and reduced contamination.</p>  <p>Smooth, nonporous surfaces are easy to sanitize and won't trap debris, breed bacteria, or absorb chemicals like wood bins.</p>	<p>Improved pack out.</p>  <p>Rounded corners and smooth surfaces mean fewer scuffs, abrasions, and cuts on your product.</p>	<p>Improved traceability and bin security.</p>  <p>Several identification methods including RFID tags and attractive foil embossing are available.</p>

Specifications for the MacroBin 26 Series

Load Capacity:	1,300 pounds
Volume Capacity:	49,603 cubic inches (+/- 4%)
Tare Weight:	87.5 pounds
Maximum Stack Weight ¹ :	12,000 pounds (long term, ambient temperature) 13,000 pounds [short term (<1 month), ambient temperature] 15,000 pounds [long term, cold storage (0° F to 35° F) ²]
Molding Process:	High-pressure injection molding
Material:	Polypropylene, U.V. stabilized
Approval:	FDA-regulated material
Container Design:	Double wall corner and center posts
Foot Design:	Two full-length feet with positive interlocking feature
Ventilation Slots:	1 ¾" (L) x 5/16" (W) in sides 1 ¼" (L) x 5/16" (W) in base Over 600 air vents in sides and base for uniform air flow; rounded surfaces on interior edges of slots
Fork Lift Entry:	Two-way: 3" opening with patented integral slide-entry
Handholds:	Two
Label Holders:	Two
External Dimensions:	47 ¾" (L) x 47 ¾" (W) x 28 ½" (H)
Internal Dimensions:	44 ½" (L) x 44 ¾" (W) x 24" (H)
Options:	Narrow Vents (3/16" wide) in the 26-a-FV MacroLid®

Notes: Dimensions assume tolerance of 1/4". Volume capacities assume tolerance of 5% and tare weights assume a tolerance of 4% unless noted otherwise. Ambient temperature approximately equal to 75° F. Data is subject to change.

¹ Stack Weight = (weight of bin contents + tare weight of bin) X number of bins in stack

² Please contact Macro Plastics if storage temperature is below 0° F.

Please refer to the appropriate User Guide for information on the safe transportation, stacking and handling of Macro Plastics products. The User Guides in PDF format are available online at www.macroplastics.com or call us at 1-800-845-6555.



MACROPLASTICS™
Inventing Fresh Ideas.

800.845.6555 | info@macroplastics.com
www.macroplastics.com