

ProBin™ 26 Series



26-S The ProBin 26-S is produced with the latest high-pressure injection molding technology, so it's durable, lightweight, and easy to handle.

The ProBin 26-S is a solid bin that works well for pickling, brining, and other liquid applications. Designed with a square footprint and two full-length feet with a positive interlocking feature, this lightweight bin is easy to move, align, and stack in storage.

Feature Highlights

- **Injection-molded, high impact resistant plastic** stands up to heavy day-to-day use. The one-piece design eliminates the problem of product getting trapped between the side walls and base.
- **Splinter-resistant plastic** eliminates contamination problems associated with wood chunks, paint chips, or metal fragments. Bin repair is inexpensive with hot air welding.
- **FDA-approved materials** are certified safe for use with food products, eliminating many HACCP problems associated with wood bins.
- **Lightweight construction** reduces shipping costs and makes ProBins easier to move; their interlocking foot design makes them safer to stack — up to 10 high.*
- **Nonporous surfaces** won't absorb water or dehydrate your product like wood bins, and they provide a constant tare weight throughout their use.
- **Rounded corners and smooth surfaces** mean fewer scuffs, abrasions, and cuts on your product. Risk of contamination is reduced because there are fewer places for unwanted particles to hide.
- **Easy-to-sanitize** ProBins keep cleaning costs to a minimum. A high-pressure wash removes most debris; a nonabrasive brush can dislodge any remaining items.

*See reverse for maximum stack weight specifications.



800.845.6555 www.macroplastics.com

Benefits of Using ProBins

<p>Increased productivity.</p>  <p>ProBins are easy to handle, move, and transport; the unique interlocking foot design makes them easy to align, stack, and store.</p>	<p>Improved pack out.</p>  <p>Rounded corners and smooth surfaces mean fewer scuffs, abrasions, and cuts on your product.</p>	<p>Reduced bin repair costs.</p>  <p>ProBins are virtually maintenance free; repairs are easy with hot air welding.</p>
<p>Better sanitation and reduced contamination.</p>  <p>Smooth, nonporous surfaces are easy to sanitize and won't trap debris, breed bacteria, or absorb chemicals like wood bins.</p>	<p>Improved traceability and bin security.</p>  <p>Several identification methods including RFID tags and attractive foil embossing are available.</p>	

Specifications for the ProBin 26-S

Load Capacity:	1,300 pounds
Volume Capacity:	49,603 cubic inches (+/- 4%) / 215 gallons
Tare Weight:	92 pounds
Maximum Stack Weight ¹ :	12,000 pounds (long term, ambient temperature) 13,000 pounds [short term (<1 month), ambient temperature] 15,000 pounds [long term, cold storage (0° F to 35° F) ²]
Molding Process:	High-pressure injection molding
Material:	Polypropylene, U.V. stabilized
Approval:	FDA-regulated material
Container Design:	Double wall corner and center posts
Foot Design:	Two full-length feet with positive interlocking feature
Fork Lift Entry:	Two-way: 3" opening with patented integral slide-entry
Handholds:	Two
Label Holders:	Two
External Dimensions:	47 3/4" (L) x 47 3/4" (W) x 28 1/2" (H)
Internal Dimensions:	44 1/2" (L) x 44 3/8" (W) x 24" (H)
Options:	MacroLid® Customer identification with RFID tags or foil embossing

Notes: Dimensions assume tolerance of 1/4". Volume capacities assume tolerance of 5% and tare weights assume a tolerance of 4% unless noted otherwise. Ambient temperature approximately equal to 75° F. Data is subject to change.

¹ Stack Weight = (weight of bin contents + tare weight of bin) X number of bins in stack

² Please contact Macro Plastics if storage temperature is below 0° F.

Please refer to the appropriate User Guide for information on the safe transportation, stacking and handling of Macro Plastics products. The User Guides in PDF format are available online at www.macroplastics.com or call us at 1-800-845-6555.



800.845.6555 | info@macroplastics.com
www.macroplastics.com