

# ProBin™ 26 Series



**26-a-S** The ProBin 26-a-S is produced with the latest high-pressure injection molding technology, so it's durable, lightweight, and easy to handle.

The ProBin 26-a-S is a solid bin that works well for pickling, brining, and other liquid applications. Designed with a square footprint and two full-length feet with a positive interlocking feature, this lightweight bin is easy to move, align, and stack in storage.

## Feature Highlights

- **Injection-molded, high impact resistant plastic** stands up to heavy day-to-day use. The one-piece design eliminates the problem of product getting trapped between the side walls and base.
- **Splinter-resistant plastic** eliminates contamination problems associated with wood chunks, paint chips, or metal fragments. Bin repair is inexpensive with hot air welding.
- **FDA-approved materials** are certified safe for use with food products, eliminating many HACCP problems associated with wood bins.
- **Lightweight construction** reduces shipping costs and makes ProBins easier to move; their interlocking foot design makes them safer to stack — up to 10 high.\*
- **Nonporous surfaces** won't absorb water or dehydrate your product like wood bins, and they provide a constant tare weight throughout their use.
- **Rounded corners and smooth surfaces** mean fewer scuffs, abrasions, and cuts on your product. Risk of contamination is reduced because there are fewer places for unwanted particles to hide.
- **Easy-to-sanitize** ProBins keep cleaning costs to a minimum. A high-pressure wash removes most debris; a nonabrasive brush can dislodge any remaining items.






\*See reverse for maximum stack weight specifications.



**MACROPLASTICS™**  
Inventing Fresh Ideas.

800.845.6555 [www.macroplastics.com](http://www.macroplastics.com)

# Benefits of Using ProBins

<p><b>Increased productivity.</b></p>  <p>ProBins are easy to handle, move, and transport; the unique interlocking foot design makes them easy to align, stack, and store.</p>	<p><b>Improved pack out.</b></p>  <p>Rounded corners and smooth surfaces mean fewer scuffs, abrasions, and cuts on your product.</p>	<p><b>Reduced bin repair costs.</b></p>  <p>ProBins are virtually maintenance free; repairs are easy with hot air welding.</p>
<p><b>Better sanitation and reduced contamination.</b></p>  <p>Smooth, nonporous surfaces are easy to sanitize and won't trap debris, breed bacteria, or absorb chemicals like wood bins.</p>	<p><b>Improved traceability and bin security.</b></p>  <p>Several identification methods including RFID tags and attractive foil embossing are available.</p>	

## Specifications for the ProBin 26-a-5

Load Capacity:	1,300 pounds
Volume Capacity:	49,603 cubic inches (+/- 4%) / 215 gallons
Tare Weight:	92 pounds
Maximum Stack Weight <sup>1</sup> :	12,000 pounds (long term, ambient temperature) 13,000 pounds [short term (<1 month), ambient temperature] 15,000 pounds [long term, cold storage (0° F to 35° F) <sup>2</sup> ]
Molding Process:	High-pressure injection molding
Material:	Polypropylene, U.V. stabilized
Approval:	FDA-regulated material
Container Design:	Double wall corner and center posts
Foot Design:	Two full-length feet with positive interlocking feature
Fork Lift Entry:	Two-way: 3" opening with patented integral slide-entry
Handholds:	Two
Label Holders:	Two
External Dimensions:	47 ¾" (L) x 47 ¾" (W) x 28 ½" (H)
Internal Dimensions:	44 ½" (L) x 44 ¾" (W) x 24" (H)
Options:	MacroLid® Customer identification with RFID tags or foil embossing

Notes: Dimensions assume tolerance of 1/4". Volume capacities assume tolerance of 5% and tare weights assume a tolerance of 4% unless noted otherwise. Ambient temperature approximately equal to 75° F. Data is subject to change.

<sup>1</sup> Stack Weight = (weight of bin contents + tare weight of bin) X number of bins in stack

<sup>2</sup> Please contact Macro Plastics if storage temperature is below 0° F.

Please refer to the appropriate User Guide for information on the safe transportation, stacking and handling of Macro Plastics products. The User Guides in PDF format are available online at [www.macroplastics.com](http://www.macroplastics.com) or call us at 1-800-845-6555.



800.845.6555 | [info@macroplastics.com](mailto:info@macroplastics.com)  
[www.macroplastics.com](http://www.macroplastics.com)